



8 Port Coaxial Cable Taps

...competitive technologies
with compelling value

Features:

- Solder back for excellent shielding
- 5-1,000 MHz Frequency range
- Integrated grounding screw
- Wall mounting screws included
- High Isolation
- 11, 14, 17, 20, 23, 26, 29, 32 & 35 dB Values available
- 11 dB Model is terminated (no through port)

Ordering Information

- CTGT8-11 11 dB (Terminating)
- CTGT8-14 14 dB
- CTGT8-17 17 dB
- CTGT8-20 20 dB
- CTGT8-23 23 dB
- CTGT8-26 26 dB
- CTGT8-29 29 dB
- CTGT8-32 32 dB
- CTGT8-35 35 dB



		11 dB	14 dB	17 dB	20 dB	23 dB	26 dB	29 dB	32 dB	35 dB
Insertion Loss	5-50 MHz	NA	3.5 dB	1.9 dB	1.2 dB	0.8 dB	0.8 dB	0.7 dB	0.7 dB	0.7 dB
	50-450 MHz	NA	4.0 dB	2.3 dB	1.5 dB	1.0 dB	0.9 dB	0.8 dB	0.8 dB	0.8 dB
	450-750 MHz	NA	4.2 dB	2.4 dB	1.8 dB	1.2 dB	1.0 dB	1.0 dB	1.0 dB	1.0 dB
	750-1000 MHz	NA	4.5 dB	2.5 dB	2.0 dB	1.4 dB	1.2 dB	1.0 dB	1.0 dB	1.0 dB
Return Loss (In / Out)	5-10 MHz	18 dB	18 dB	16 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB
	10-50 MHz	20 dB	20 dB	18 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB
	50-450 MHz	20 dB	20 dB	18 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB
	450-750 MHz	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB
	750-1000 MHz	16 dB	16 dB	16 dB	16 dB	16 dB	16 dB	16 dB	16 dB	16 dB
Return Loss (Tap)	5-50 MHz	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB
	50-750 MHz	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB	20 dB
	750-1000 MHz	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB	18 dB
Isolation (Tap / Tap)	5-50 MHz	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB
	50-450 MHz	26 dB	26 dB	26 dB	26 dB	26 dB	26 dB	26 dB	26 dB	26 dB
	450-750 MHz	25 dB	25 dB	25 dB	25 dB	25 dB	25 dB	25 dB	25 dB	25 dB
	750-1000 MHz	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB	22 dB
Isolation (Out / Tap)	5-10 MHz	NA	30 dB	28 dB	36 dB	36 dB	38 dB	38 dB	38 dB	38 dB
	10-50 MHz	NA	30 dB	28 dB	35 dB	36 dB	35 dB	36 dB	36 dB	36 dB
	50-450 MHz	NA	26 dB	25 dB	32 dB	33 dB	32 dB	32 dB	32 dB	32 dB
	450-750 MHz	NA	24 dB	24 dB	30 dB	30 dB	30 dB	30 dB	30 dB	30 dB
	750-1000 MHz	NA	24 dB	24 dB	26 dB	26 dB	28 dB	28 dB	28 dB	30 dB
Tap Tolerance (+/-)	5-450 MHz	1.0 dB	1.0 dB	1.0 dB	1.0 dB	1.0 dB	1.0 dB	1.0 dB	1.0 dB	1.0 dB
	450-750 MHz	1.5 dB	1.5 dB	1.5 dB	1.5 dB	1.5 dB	1.5 dB	1.5 dB	1.5 dB	1.5 dB
	750-1000 MHz	2.0 dB	2.0 dB	2.0 dB	2.0 dB	2.0 dB	2.0 dB	2.0 dB	2.0 dB	2.0 dB

Email: sales@cabletronix.com

Web: www.cabletronix.com