



...competitive technologies
with compelling value

DA-71HP

1 x 7 Composite Video / Audio Distribution Amplifier

Features:

- Splits one composite video along with left and right audio signals to up to seven viewing locations
- All RCA connections
- Multiple units can be cascaded to provide more outputs
- Low profile, wall mountable plastic housing

Contents Include:

- 1 DA-71HP
- 1 Power supply
- 1 User's manual



Description:

The DA-71HP has been designed to distribute a single composite video source with left and right audio to up to seven viewing locations while maintaining the original signal strength after distribution. The DA-41HP can be looped, cascaded or put in tandem without loss of audio/video signals.

Video

Video Input Impedance	75ohm +5%
Gain	2 Volt unterminated 1 Volt terminated
Video Insertion Loss	50Hz to 100MHz < 0.4dB
In to Out Isolation	50Hz to 10MHz 32dB
Out to In Isolation	50Hz to 10MHz 60dB
Return Loss	50Hz to 100MHz 20dB
Video Bandwidth	>100Mhz
Video Input	1 RCA Female
Video Outputs	7 RCA Female

Audio

Gain	Unity
Audio Input Impedance	22K ohm
Audio Output Impedance	1K ohm
THD	0.05% @ 1.0 Volts input level
Frequency Response	10Hz to 50KHz + 1 dB
Channel Separation	>75dB @ 1KHz
In to Out Isolation	60dB
Out to In Isolation	60dB
Signal to Noise	100dB re 2 Volts (out)
Audio Input	1 set of L & R RCA Female
Audio Outputs	7 sets of L & R RCA Female

General

Power	9 Volt DC@600mA with 2.5mm jack
Dimensions	8.52"(W) x 3.23"(H) x 1.4"(D)
Weight	0.88 lb
Housing	Wall Mount Plastic Case

